



RSK-CR01



RSK-CR10



RSK-BIO



RSK-BIO-T



RSK-Face



RSK-Face-BIO



Reader Access Controller

GENERAL DATA						
Software Application	Software / Web-Browser					
CCTV Integration	Support CCTV NX-VMS					
Verification Mode	Card/PIN		Fingerprint/Card	Fingerprint/PIN/Card	Face Recognition/PIN/Card	Face/PIN/Card/Fingerprint
Bluetooth/ NFC (Optional)	YES / YES		NO / NO	YES / YES	YES / YES	
Display / Keypad	NO / Touch Keypad	2.8"TFT Color/Touch Keypad	NO / NO	2.8"TFT Color/Touch Keypad	4.3" TFT Touch Screen	
Proximity	EM/Mifare/HID/Desfire		EM/Mifare/HID	EM/Mifare/HID/Desfire	EM/Mifare/Desfire	
Fingerprint Template Capacity	NO		9,590		NO	9,590
Sensor Type	NO		Optical		Dual Camera Fast Recognition	
Fingerprint Sensor Resolution	NO		500 dpi		500 dpi	
Face Capacity	NO					10,000
1:N Identification Speed	NO	<760msec			<500msec	
User/Card Capacity	20,000					
Function Keys	400 Sets		NO	400 Sets	4 Touch Keys	
Communciations	TCP/IP, Weigand, RS485					
Wiegand Inputs or Outputs	26/34 Bits Wiegand Reader					
Input/Output Support	DI:3 / DO:1				DI:3 / DO:2	
Inbuil Relays	Door Lock (NO/COM/NC)				Door Lock (NO/COM/NC) & Alarm (NO/COM/NC)	
(Max. power loading)	30 VDC / 1A		40 VDC / 2A	30 VDC / 1A		
System Log/ Event Log	1,536 / 65,536 entries		1,536 / 50,000 entries		10,000 / 100,000 entries	
Time Sets/ Time Zones/ Group	255 / 120 / 255 Sets					
Holiday Set	100 Sets					
Remote Control/ Event Handle	YES / YES					
Fast Registry	YES					
Anti-Pass Back	YES				NO	
Live Face Detection	NO				YES	
Face Scan Distance	NO				30 ~ 120 cm	
ELECTRICAL DATA & COMMUNICATION						
Power Consumption	500 mA ± 5%				1,000 mA ± 5%	
Power Requirement	9 ~ 24 VDC / 1A				12 VDC / 1.5A	
Operation Temperature	0° C ~ 65° C				0° C ~ 50° C	
Operation Humidity	5% ~ 80% RH				10% ~ 80% RH	
PHYSICAL DATA						
Dimension	78.5 x 129 x 23 mm	160.2 x 140.2 x 46.7 mm	160 x 56.9 x 40.1 mm	160.2 x 140.2 x 46.7 mm	122.5 x 185 x 89 mm	160.2 x 140.2 x 46.7 mm
Weight	122 g	600 g	150 g	600 g	590 g	630 g
Protection	Weatherproof (IP65)		Indoor Used	Weatherproof (IP65)	Indoor Used	

Note: Above Specification may be change without prior notice